LIMESTONE COAST



www.dreamtimeflooring.com

TECHNICAL SPECIFICATIONS

Collection: Limestone Coast

Country of Origin: Australia

Colours: 10 Standard

Yarn: 100% BCF Yarn Dyed Nylon

Surface Texture: Textured Loop Pile

Gauge: 47.2/10cm (1/12th Gauge)

Total Product Thickness: 7 (+/- 1.0)mm

Pile Weight: 750g/m²(22oz/yd²)

Product Size: 500mm x 500mm

Backing: Enviro Bac® - Minimum 60% recycled content

Installation Method: 1/4 Turn, Brick or Ashlar

Type: Commercial Carpet Tile

Available Options: † 250mm x 1000mm - Skinny Plank^

Enviro Bac Plus® - Cushion Backed Easy Grip TM - Adhesive Free Installation

PERFORMANCE

Anti-Static: (AATCC 134) < 3.5KV at 21°C & 20% Relative Humidity

CRF 4.5kW/m² †

Flammability:
(AS ISO 9239.12003)
Smoke Value 518% Minutes (Direct Stick)

Colourfast to light: 6-7 (Minimum mandatory performance for ACCS:5)

Light Reflectance:Available on Request

Stain Resistance: Stain Warden®

Biocontaminant Control:Bioshield® Antimicrobial Control

ACCS Rating: Contact Extra Heavy & Duty & Stairs #12156 †

Contract Guarantee: 15 Years available on request*

Recommended Adhesive: Refer to our DT Commercial Adhesive Guide www.dreamtimeflooring.com

SUSTAINABILITY

PVC Minimisation: PVC Free

Indoor Air Quality: Green Building Council & Green Label Plus complaint for VOC's emission rate limits †

Product Transparency:Declare Red List Free

Green Star: Environmental Certification Scheme (ECS) Level 4

Maximum Points - Certification #13037 †

Accreditation: Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.















